

TECHNICAL DATA

	XL	TILE	PLANK
SIZES	400 mm x 800 mm	305 mm x 610 mm	185 mm x 915 mm
TOTAL THICKNESS	6.5 mm	6.5 mm	6.5 mm
EVA BACKING FOAM	2.5 mm	2.5 mm	2.5 mm
CORE MINERAL FIBER BOARD	3 mm	3 mm	3 mm
PVC PROTECTIVE COATING	1 mm	1 mm	1 mm
BEVEL	V BEVEL 4 SIDE PAINTED	V BEVEL 4 SIDE PAINTED	V BEVEL 4 SIDE PAINTED
COLOUR FASTNESS TO LIGHT ISO 105 B02:2013	4 - 5	4 - 5	4 - 5
DIMENSIONAL STABILITY ISO23999:2012	0.10 %	0.10 %	0.10 %
EXPANSION IN TEMPERATURE CHANGE FROM 23° C TO 45° C	0.010 %	0.010 %	0.010 %
SHRINKAGE IN TEMPERATURE CHANGE FROM 23° C TO 5° C	-0.047 %	-0.047 %	-0.047 %
CURLING AFTER HEAT EXPOSURE ISO23999:2012	0 mm	0 mm	0 mm
FIRE BEHAVIOR UNE-EN 13823:2012	C-s2,d0	C-s2,d0	C-s2,d0
FORMALDEHYDE EMISSIONS EN717-1:2004	PASS	PASS	PASS
SWELLING IN THICKNESS AFTER IMMERSION IN WATER EN317:1994	1 %	1 %	1 %
DETERMINATION OF RESIDUAL INDENTATION EN ISO24343-1:2012	0.04 mm	0.04 mm	0,04 mm
VOC EMISSIONS TESTING ISO:16000 / 3,6,9,11	A+	A+	A+
VOC EMISSIONS TESTING CDPH1350 (CALIFORNIA SPECIFICATION 01350)	PASS	PASS	PASS
US CALIFORNIA PROPOSITION 65 - PHTHALATE	PASS	PASS	PASS
WARRANTY RESIDENCIAL USE*	25	25	25
WARRANTY COMERCIAL USE*	10	10	10

*Check carefully the Warranty Conditions and Installation Method.

